

TYRES

Product group	Tyres
Item number	15722213
Valid tyre size	18.4 - 26
LI / SI / PR	149 A6 / 145 A8, 14 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 2001



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Suitable for agricultural work, backhoe loaders.
- Robust tyre with high number of plies.
- Reinforced casing.

Technical Informations

Item number	15722213
EAN	8903094035618
Valid tyre size	18.4 - 26
LI / SI / PR	149 A6 / 145 A8, 14 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 2001
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	97,29
Recommended rim size	W16L
Permitted rim size	W15L
Maximum air pressure [bar].	2,60
Section width (mm)	467
Outer diameter of tyre [mm].	1475
Stat. radius (SLR) [mm]	650
Rolling circumference [mm].	4250
Tread depth (mm)	38,0
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A6	3250	30		2,60	
145 A8	2900	40		2,60	