

TYRES

Product group	Tyres
Item number	15722220
Valid tyre size	23.1 - 26
LI / SI / PR	153 A6 / 149 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 135



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

Technical Informations

Item number	15722220
EAN	8903094003983
Valid tyre size	23.1 - 26
LI / SI / PR	153 A6 / 149 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	153,02
Recommended rim size	DW20B
Permitted rim size	DW20A
Maximum air pressure [bar].	1,70
Section width (mm)	587
Outer diameter of tyre [mm].	1585
Stat. radius (SLR) [mm]	700
Rolling circumference [mm].	4615
Tread depth (mm)	43,0
Number of lugs	21x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A6	3650	30		1,70	
149 A8	3250	40		1,70	