

TYRES

| | |
|-----------------|------------------------|
| Product group | Tyres |
| Item number | 15722223 |
| Valid tyre size | 23.1 - 26 |
| LI / SI / PR | 159 A6 / 155 A8, 16 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | TR 135 |



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

Technical Informations

| | |
|------------------------------|------------------------|
| Item number | 15722223 |
| EAN | 8903094004027 |
| Valid tyre size | 23.1 - 26 |
| LI / SI / PR | 159 A6 / 155 A8, 16 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | TR 135 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 156,69 |
| Recommended rim size | DW20B |
| Permitted rim size | DW20A |
| Maximum air pressure [bar]. | 2,30 |
| Section width (mm) | 587 |
| Outer diameter of tyre [mm]. | 1585 |
| Stat. radius (SLR) [mm] | 700 |
| Rolling circumference [mm]. | 4615 |
| Tread depth (mm) | 43,0 |
| Number of lugs | 21x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 159 A6 | 4375 | 30 | | 2,30 | |
| 155 A8 | 3875 | 40 | | 2,30 | |