

TYRES

Product group	Tyres
Item number	15722232
Valid tyre size	23.1 - 26
LI / SI / PR	172 A2 / 160 A6, 16 PR
TL/TT	TT
Brand	BKT
Tread pattern	FS 216



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- For log skidders and skidders
- Rugged lug design for very good traction
- Steel belt construction with nylon casing to protect against punctures
- Reinforced sidewall and bead protection

Technical Informations

Item number	15722232
EAN	8903094031795
Valid tyre size	23.1 - 26
LI / SI / PR	172 A2 / 160 A6, 16 PR
TL/TT	TT
Brand	BKT
Tread pattern	FS 216
TRA Code	LS-2
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	233,56
Recommended rim size	20
Maximum air pressure [bar].	2,40
Section width (mm)	587
Outer diameter of tyre [mm].	1615
Stat. radius (SLR) [mm]	726
Rolling circumference [mm].	4780
Tread depth (mm)	55,0
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A2	6300	10		2,40	
160 A6	4500	30		2,40	