

TYRES

Product group	Tyres
Item number	15722245
Valid tyre size	18.4 - 30
LI / SI / PR	155 A2 / 143 A6, 10 PR
TL/TT	TT
Brand	BKT
Tread pattern	FS 216



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- For log skidders and skidders
- Rugged lug design for very good traction
- Steel belt construction with nylon casing to protect against punctures
- Reinforced sidewall and bead protection

Technical Informations

Item number	15722245
EAN	8903094028115
Valid tyre size	18.4 - 30
LI / SI / PR	155 A2 / 143 A6, 10 PR
TL/TT	TT
Brand	BKT
Tread pattern	FS 216
TRA Code	LS-2
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	163,63
Recommended rim size	DW16A
Maximum air pressure [bar].	1,70
Section width (mm)	467
Outer diameter of tyre [mm].	1577
Stat. radius (SLR) [mm]	724
Rolling circumference [mm].	4736
Tread depth (mm)	52,0
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A2	3875	10		1,70	
143 A6	2725	30		1,70	