

TYRES

Product group	Tyres
Item number	15722301
Valid tyre size	8.3 - 28
LI / SI / PR	108 A6 / 104 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

Technical Informations

Item number	15722301
EAN	8903094004614
Valid tyre size	8.3 - 28
LI / SI / PR	108 A6 / 104 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	23,75
Recommended rim size	W7
Permitted rim size	W6
Maximum air pressure [bar].	3,20
Section width (mm)	213
Outer diameter of tyre [mm].	1104
Stat. radius (SLR) [mm]	519
Rolling circumference [mm].	3347
Tread depth (mm)	27,5
Number of lugs	23x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
108 A6	1000	30		3,20	
104 A8	900	40		3,20	