

TYRES

Product group	Tyres
Item number	15722310
Valid tyre size	11.2 - 28
LI / SI / PR	118 A6 / 114 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

Technical Informations

Item number	15722310
EAN	8903094003075
Valid tyre size	11.2 - 28
LI / SI / PR	118 A6 / 114 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	36,15
Recommended rim size	W10
Permitted rim size	W9
Maximum air pressure [bar].	2,40
Section width (mm)	284
Outer diameter of tyre [mm].	1205
Stat. radius (SLR) [mm]	565
Rolling circumference [mm].	3543
Tread depth (mm)	33,0
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
118 A6	1320	30		2,40	
114 A8	1180	40		2,40	