

## TYRES

Product group	Tyres
Item number	15722415
Valid tyre size	14.9 - 28
LI / SI / PR	137 A6 / 133 A8, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp  
■ ■ ● Moving Professionals

**BKT**  
GROWING TOGETHER

## Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

## Technical Informations

Item number	15722415
EAN	8903094003525
Valid tyre size	14.9 - 28
LI / SI / PR	137 A6 / 133 A8, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	68,63
Recommended rim size	W13
Permitted rim size	W11, W12
Maximum air pressure [bar].	2,60
Section width (mm)	378
Outer diameter of tyre [mm].	1365
Stat. radius (SLR) [mm]	634
Rolling circumference [mm].	4170
Tread depth (mm)	36,0
Number of lugs	18x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
137 A6	2300	30		2,60	
133 A8	2060	40		2,60	