

TYRES

Product group	Tyres
Item number	15722430
Valid tyre size	16.9 - 28
LI / SI / PR	135 A6 / 131 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 2001



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Suitable for agricultural work, backhoe loaders.
- Robust tyre with high number of plies.
- Reinforced casing.

Technical Informations

Item number	15722430
EAN	8903094002689
Valid tyre size	16.9 - 28
LI / SI / PR	135 A6 / 131 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 2001
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	80,51
Recommended rim size	W15L
Permitted rim size	W14L
Maximum air pressure [bar].	1,70
Section width (mm)	429
Outer diameter of tyre [mm].	1420
Stat. radius (SLR) [mm]	651
Rolling circumference [mm].	4319
Tread depth (mm)	40,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	310
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 A6	2180	30		1,70	
131 A8	1950	40		1,70	