

## TYRES

Product group	Tyres
Item number	15722440
Valid tyre size	16.9 - 28
LI / SI / PR	152 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 459



## Notes and features

- The strong nylon carcass & the special rubber compound make the tyre particularly resistant to breaks, punctures & similar damage.
- Extra wide and overlapping lugs in the center of the tread.
- Ideal for industrial use such as on backhoe loaders.

## Technical Informations

Item number	15722440
EAN	8903094016556
Valid tyre size	16.9 - 28
LI / SI / PR	152 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 459
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	91,00
Recommended rim size	DW15L
Permitted rim size	DW14L
Maximum air pressure [bar].	2,60
Section width (mm)	440
Outer diameter of tyre [mm].	1410
Stat. radius (SLR) [mm]	640
Rolling circumference [mm].	4145
Tread depth (mm)	28,0
Number of lugs	18x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A8	3550	40		2,60	