

## TYRES

Product group	Tyres
Item number	15722470
Valid tyre size	18.4 - 30
LI / SI / PR	149 A6 / 145 A8, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp  
■ ■ ● Moving Professionals

**BKT**  
GROWING TOGETHER

## Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

## Technical Informations

Item number	15722470
EAN	8903094003785
Valid tyre size	18.4 - 30
LI / SI / PR	149 A6 / 145 A8, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	94,67
Recommended rim size	W16L
Permitted rim size	W15L
Maximum air pressure [bar].	2,30
Section width (mm)	460
Outer diameter of tyre [mm].	1545
Stat. radius (SLR) [mm]	697
Rolling circumference [mm].	4712
Tread depth (mm)	38,0
Number of lugs	19x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A6	3250	30		2,30	
145 A8	2900	40		2,30	