

TYRES

Product group	Tyres
Item number	15722480
Valid tyre size	23.1 - 30
LI / SI / PR	155 A6 / 151 A8, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

Technical Informations

Item number	15722480
EAN	8903094004058
Valid tyre size	23.1 - 30
LI / SI / PR	155 A6 / 151 A8, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	156,72
Recommended rim size	DW20B
Maximum air pressure [bar].	1,70
Section width (mm)	600
Outer diameter of tyre [mm].	1700
Stat. radius (SLR) [mm]	780
Rolling circumference [mm].	4998
Tread depth (mm)	43,0
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A6	3875	30		1,70	
151 A8	3450	40		1,70	