

TYRES

Product group	Tyres
Item number	15722562
Valid tyre size	24.5 - 32
LI / SI / PR	163 A6 / 159 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 137



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Ideal for use on harvesting machines.
- Robust tyre with low cross-section.
- Wide base tyre with excellent traction.
- Its special belt version provides additional puncture resistance.
- A special rubber compound, super strong casing and perfect tread pattern depth ensure the exceptional durability of the TR 137.

Technical Informations

Item number	15722562
EAN	8903094004324
Valid tyre size	24.5 - 32
LI / SI / PR	163 A6 / 159 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 137
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	217,83
Recommended rim size	DW21B
Permitted rim size	DW20B
Maximum air pressure [bar].	2,00
Section width (mm)	622
Outer diameter of tyre [mm].	1805
Stat. radius (SLR) [mm]	807
Rolling circumference [mm].	5343
Tread depth (mm)	42,0
Number of lugs	24x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
163 A6	4875	30		2,00	
159 A8	4375	40		2,00	