

TYRES

| | |
|-----------------|------------------------|
| Product group | Tyres |
| Item number | 15722570 |
| Valid tyre size | 30.5L - 32 |
| LI / SI / PR | 162 A6 / 158 A8, 12 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | TR 137 |



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Ideal for use on harvesting machines.
- Robust tyre with low cross-section.
- Wide base tyre with excellent traction.
- Its special belt version provides additional puncture resistance.
- A special rubber compound, super strong casing and perfect tread pattern depth ensure the exceptional durability of the TR 137.

Technical Informations

| | |
|------------------------------|------------------------|
| Item number | 15722570 |
| EAN | 8903094004331 |
| Valid tyre size | 30.5L - 32 |
| LI / SI / PR | 162 A6 / 158 A8, 12 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | TR 137 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 280,05 |
| Recommended rim size | DH27B |
| Permitted rim size | DW27B |
| Maximum air pressure [bar]. | 1,40 |
| Section width (mm) | 770 |
| Outer diameter of tyre [mm]. | 1865 |
| Stat. radius (SLR) [mm] | 831 |
| Rolling circumference [mm]. | 5520 |
| Tread depth (mm) | 48,0 |
| Number of lugs | 22x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 162 A6 | 4750 | 30 | | 1,40 | |
| 158 A8 | 4250 | 40 | | 1,40 | |