

TYRES

Product group	Tyres
Item number	15722572
Valid tyre size	30.5L - 32
LI / SI / PR	170 A6 / 167 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 137



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Ideal for use on harvesting machines.
- Robust tyre with low cross-section.
- Wide base tyre with excellent traction.
- Its special belt version provides additional puncture resistance.
- A special rubber compound, super strong casing and perfect tread pattern depth ensure the exceptional durability of the TR 137.

Technical Informations

Item number	15722572
EAN	8903094004355
Valid tyre size	30.5L - 32
LI / SI / PR	170 A6 / 167 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 137
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	293,84
Recommended rim size	DH27B
Permitted rim size	DW27B
Maximum air pressure [bar].	2,10
Section width (mm)	770
Outer diameter of tyre [mm].	1865
Stat. radius (SLR) [mm]	831
Rolling circumference [mm].	5520
Tread depth (mm)	48,0
Number of lugs	22x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 A6	6000	30		2,10	
167 A8	5450	40		2,10	