

TYRES

Product group	Tyres
Item number	15722580
Valid tyre size	30.5L - 32
LI / SI / PR	166 A6, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	FS 216



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- For log skidders and skidders
- Rugged lug design for very good traction
- Steel belt construction with nylon casing to protect against punctures
- Reinforced sidewall and bead protection

Technical Informations

Item number	15722580
EAN	8903094027620
Valid tyre size	30.5L - 32
LI / SI / PR	166 A6, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	FS 216
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	448,02
Recommended rim size	DH27
Permitted rim size	DH27B
Maximum air pressure [bar].	1,70
Section width (mm)	775
Outer diameter of tyre [mm].	1847
Stat. radius (SLR) [mm]	833
Rolling circumference [mm].	5466
Tread depth (mm)	58,0
Number of lugs	16x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 A6	5300	30		1,70	