

TYRES

Product group	Tyres
Item number	15722590
Valid tyre size	35.5L - 32
LI / SI / PR	177 A6, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	FS 216
Sonderpostenkategorie	DOT
type of damage	DOT



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- For log skidders and skidders
- Rugged lug design for very good traction
- Steel belt construction with nylon casing to protect against punctures
- Reinforced sidewall and bead protection

Technical Informations

Item number	15722590
Valid tyre size	35.5L - 32
LI / SI / PR	177 A6, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	FS 216
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	608,08
Recommended rim size	DH31
Permitted rim size	DH31H
Maximum air pressure [bar].	2,10
Section width (mm)	907
Outer diameter of tyre [mm].	2011
Stat. radius (SLR) [mm]	912
Rolling circumference [mm].	5992
Tread depth (mm)	62,0
Number of lugs	16x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
177 A6	7300	30		1,70	
	10200	10		2,10	