

TYRES

Product group	Tyres
Item number	15722612
Valid tyre size	18.4 - 34
LI / SI / PR	154 A6 / 150 A8, 14 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

Technical Informations

Item number	15722612
EAN	8903094004126
Valid tyre size	18.4 - 34
LI / SI / PR	154 A6 / 150 A8, 14 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	116,01
Recommended rim size	W16L
Permitted rim size	W15L
Maximum air pressure [bar].	2,60
Section width (mm)	467
Outer diameter of tyre [mm].	1650
Stat. radius (SLR) [mm]	751
Rolling circumference [mm].	5009
Tread depth (mm)	38,0
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 A6	3750	30		1,60	
150 A8	3350	40		2,60	