

TYRES

Product group	Tyres
Item number	15722760
Valid tyre size	13.6 - 38
LI / SI / PR	131 A6 / 127 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

Technical Informations

Item number	15722760
EAN	8903094003419
Valid tyre size	13.6 - 38
Alternative size 1	14.00-38
LI / SI / PR	131 A6 / 127 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	66,97
Recommended rim size	W12
Permitted rim size	W11
Maximum air pressure [bar].	2,00
Section width (mm)	345
Outer diameter of tyre [mm].	1565
Stat. radius (SLR) [mm]	735
Rolling circumference [mm].	4832
Tread depth (mm)	36,0
Number of lugs	23x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
131 A6	1950	30		2,00	
127 A8	1750	40		2,00	