

## TYRES

|                 |                       |
|-----------------|-----------------------|
| Product group   | Tyres                 |
| Item number     | 15722770              |
| Valid tyre size | 16.9 - 38             |
| LI / SI / PR    | 141 A6 / 137 A8, 8 PR |
| TL/TT           | TT                    |
| Brand           | BKT                   |
| Tread pattern   | TR 135                |



Bohnenkamp  
■ ■ ● Moving Professionals

**BKT**  
GROWING TOGETHER

## Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

## Technical Informations

|                              |                       |
|------------------------------|-----------------------|
| Item number                  | 15722770              |
| EAN                          | 8903094003730         |
| Valid tyre size              | 16.9 - 38             |
| LI / SI / PR                 | 141 A6 / 137 A8, 8 PR |
| TL/TT                        | TT                    |
| Brand                        | BKT                   |
| Tread pattern                | TR 135                |
| Antistatic                   | No                    |
| Tyre colour                  | Black                 |
| ECE regulation number        | ECE 106               |
| Nettogewicht [kg] (gültig)   | 101,87                |
| Recommended rim size         | W15L                  |
| Permitted rim size           | W14L                  |
| Maximum air pressure [bar].  | 1,70                  |
| Section width (mm)           | 429                   |
| Outer diameter of tyre [mm]. | 1685                  |
| Stat. radius (SLR) [mm]      | 788                   |
| Rolling circumference [mm].  | 4954                  |
| Tread depth (mm)             | 38,0                  |
| Number of lugs               | 21x2                  |
| E-Ready                      | No                    |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 141 A6 | 2575               | 30           |               | 1,70                     |              |
| 137 A8 | 2300               | 40           |               | 1,70                     |              |