

## TYRES

Product group	Tyres
Item number	15722795
Valid tyre size	9.5 - 42
LI / SI / PR	125 A6 / 121 A8, 10 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135



Bohnenkamp  
■ ■ ● Moving Professionals

**BKT**  
GROWING TOGETHER

## Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

## Technical Informations

Item number	15722795
EAN	8903094030361
Valid tyre size	9.5 - 42
LI / SI / PR	125 A6 / 121 A8, 10 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 135
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	48,47
Recommended rim size	W8
Permitted rim size	W7
Maximum air pressure [bar].	3,50
Section width (mm)	246
Outer diameter of tyre [mm].	1510
Stat. radius (SLR) [mm]	721
Rolling circumference [mm].	4663
Tread depth (mm)	31,0
Number of lugs	29x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
125 A6	1650	30		3,50	
121 A8	1450	40		3,50	