

TYRES

Product group	Tyres
Item number	15722825
Valid tyre size	20.8 - 42
LI / SI / PR	168 A6 / 164 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 135



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications.
- Some sizes and versions are suitable for use on excavators, trailers or harvesters.
- The double angled lugs provide excellent traction.
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions.
- The lugs overlapping in the tread centre ensure comfortable handling on the road.

Technical Informations

Item number	15722825
EAN	8903094062751
Valid tyre size	20.8 - 42
LI / SI / PR	168 A6 / 164 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 135
Carcass properties	Dual Bead
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	184,30
Recommended rim size	W18L
Permitted rim size	W16L
Maximum air pressure [bar].	3,20
Section width (mm)	535
Outer diameter of tyre [mm].	1950
Stat. radius (SLR) [mm]	909
Speed Radius Index (SRI)	600
Rolling circumference [mm].	5733
Tread depth (mm)	42,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A6	5600	30		3,20	
164 A8	5000	40		3,20	