

TYRES

Product group	Tyres
Item number	15726015
Valid tyre size	180 / 95 R 16
LI / SI / PR	105 A8 / 105 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726015
EAN	8903094039210
Valid tyre size	180 / 95 R 16
Alternative size 1	6.50R16
LI / SI / PR	105 A8 / 105 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	17,05
Recommended rim size	5.5F
Permitted rim size	6.0F
Maximum air pressure [bar].	3,20
Section width (mm)	185
Outer diameter of tyre [mm].	760
Stat. radius (SLR) [mm]	340
Rolling circumference [mm].	2265
Tread depth (mm)	23,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	33.1
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
105 A8	925	40		3,20	
105 B	925	50		3,20	