

TYRES

Product group	Tyres
Item number	15726025
Valid tyre size	210 / 95 R 16
LI / SI / PR	106 A8 / 106 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726025
EAN	8903094028665
Valid tyre size	210 / 95 R 16
Alternative size 1	7.50R16
LI / SI / PR	106 A8 / 106 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	21,14
Recommended rim size	W7
Permitted rim size	W6, 6LB
Maximum air pressure [bar].	2,40
Section width (mm)	214
Outer diameter of tyre [mm].	806
Stat. radius (SLR) [mm]	360
Rolling circumference [mm].	2415
Tread depth (mm)	27,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	34.85
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
106 A8	950	40		2,40	
106 B	950	50		2,40	