

## TYRES

Product group	Tyres
Item number	15726042
Valid tyre size	210 / 95 R 20
LI / SI / PR	110 A8 / 110 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

## Technical Informations

Item number	15726042
EAN	8903094043804
Valid tyre size	210 / 95 R 20
Alternative size 1	8.3R20
LI / SI / PR	110 A8 / 110 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	24,66
Recommended rim size	W7
Permitted rim size	W6
Maximum air pressure [bar].	2,40
Section width (mm)	214
Outer diameter of tyre [mm].	908
Stat. radius (SLR) [mm]	418
Rolling circumference [mm].	2749
Tread depth (mm)	34,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	43.79
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
110 A8	1060	40		2,40	
110 B	1060	50		2,40	