

TYRES

Product group	Tyres
Item number	15726045
Valid tyre size	250 / 85 R 20
LI / SI / PR	116 A8 / 116 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726045
EAN	8903094027460
Valid tyre size	250 / 85 R 20
Alternative size 1	9.5R20
LI / SI / PR	116 A8 / 116 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	28,86
Recommended rim size	W8
Permitted rim size	W7, W9
Maximum air pressure [bar].	2,40
Section width (mm)	250
Outer diameter of tyre [mm].	940
Stat. radius (SLR) [mm]	424
Rolling circumference [mm].	2812
Tread depth (mm)	37,0
Number of lugs	17x2
Lug width (mm)	26
Tyre capacity 75% [ltr.]	55.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
116 A8	1250	40		2,40	
116 B	1250	50		2,40	