

TYRES

Product group	Tyres	
Item number	15726060	
Valid tyre size	14.9 L R 20	
LI / SI / PR	119 A8 / 119 B	
TL/TT	TL	
Brand	BKT	
Tread pattern	Agrimax RT 851	



Notes and features

- The BKT Agrimax RT 851 was developed for tractors in grassland applications.
- Lugs with rounded shoulders reduce damage to grasslands and emerging crops.
- Its strong nylon casing with sturdy polyester belts provides high durability and a long service life.
- The tyre is characterised by ultra-low soil compaction and excellent self-cleaning properties.



Technical Informations

	45700000
Item number	15726060
EAN	8903094048632
Valid tyre size	14.9 L R 20
Alternative size 1	375/75R20
LI / SI / PR	119 A8 / 119 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 851
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	57,18
Recommended rim size	W13
Permitted rim size	W11, W12, W14
Maximum air pressure [bar].	1,60
Section width (mm)	378
Outer diameter of tyre [mm].	1100
Stat. radius (SLR) [mm]	498
Rolling circumference [mm].	3286
Tread depth (mm)	32,0
Number of lugs	17x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
119 A8	1360	40		1,60	
119 B	1360	50		1,60	