

## TYRES

Product group	Tyres
Item number	15726085
Valid tyre size	250 / 85 R 24
LI / SI / PR	109 A8 / 109 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

## Technical Informations

Item number	15726085
EAN	8903094028177
Valid tyre size	250 / 85 R 24
Alternative size 1	9.5R24
LI / SI / PR	109 A8 / 109 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	34,43
Recommended rim size	W8
Permitted rim size	W7, W9
Maximum air pressure [bar].	1,60
Section width (mm)	251
Outer diameter of tyre [mm].	1036
Stat. radius (SLR) [mm]	475
Rolling circumference [mm].	3104
Tread depth (mm)	37,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	63.75
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
109 A8	1030	40		1,60	
109 B	1030	50		1,60	