

## TYRES

Product group	Tyres
Item number	15726090
Valid tyre size	280 / 85 R 24
LI / SI / PR	115 A8 / 115 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

## Technical Informations

Item number	15726090
EAN	8903094021536
Valid tyre size	280 / 85 R 24
Alternative size 1	11.2R24
LI / SI / PR	115 A8 / 115 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	43,66
Recommended rim size	W10
Permitted rim size	W9
Maximum air pressure [bar].	1,60
Section width (mm)	292
Outer diameter of tyre [mm].	1086
Stat. radius (SLR) [mm]	492
Rolling circumference [mm].	3224
Tread depth (mm)	41,0
Number of lugs	19x2
Lug width (mm)	29
Tyre capacity 75% [litr.]	79.5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
115 A8	1215	40		1,60	
115 B	1215	50		1,60	