

TYRES

Product group	Tyres
Item number	15726100
Valid tyre size	320 / 85 R 24
LI / SI / PR	122 A8 / 122 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726100
EAN	8903094021550
Valid tyre size	320 / 85 R 24
Alternative size 1	12.4R24
LI / SI / PR	122 A8 / 122 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	54,82
Recommended rim size	W11
Permitted rim size	W9, W10
Maximum air pressure [bar].	1,60
Section width (mm)	329
Outer diameter of tyre [mm].	1154
Stat. radius (SLR) [mm]	519
Rolling circumference [mm].	3424
Tread depth (mm)	42,0
Number of lugs	18x2
Lug width (mm)	31
Tyre capacity 75% [litr.]	111.75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
122 A8	1500	40		1,60	
122 B	1500	50		1,60	