

## TYRES

Product group	Tyres
Item number	15726147
Valid tyre size	420 / 85 R 26
LI / SI / PR	138 A8 / 138 B
TL/TT	TL
Brand	BKT
Tread pattern	RT 857



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- RT 857 is suitable for use on medium-power tractors.
- It has very good driving performance during transportation
- The high load-bearing capacity of the polyester belt plies and the special stubble guard rubber compound make the tyre robust and protect it from impact damage

## Technical Informations

Item number	15726147
EAN	8903094045013
Valid tyre size	420 / 85 R 26
Alternative size 1	16.9R26
LI / SI / PR	138 A8 / 138 B
TL/TT	TL
Brand	BKT
Tread pattern	RT 857
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	95,16
Recommended rim size	DW15L
Permitted rim size	W14L, W15L, W16L,DW16L
Maximum air pressure [bar].	1,60
Section width (mm)	438
Outer diameter of tyre [mm].	1374
Stat. radius (SLR) [mm]	616
Rolling circumference [mm].	4115
Tread depth (mm)	34,0
Number of lugs	20x2
Lug width (mm)	40
Tyre capacity 75% [ltr.]	263.27
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 A8	2360	40		1,60	
138 B	2360	50		1,60	