

TYRES

Product group	Tyres
Item number	15726149
Valid tyre size	460 / 85 R 26
LI / SI / PR	143 A8 / 143 B
TL/TT	TL
Brand	BKT
Tread pattern	RT 857





Notes and features

- RT 857 is suitable for use on medium-power tractors.
- It has very good driving performance during transportation
- The high load-bearing capacity of the polyester belt plies and the special stubble guard rubber compound make the tyre robust and protect it from impact damage



Technical Informations

Item number	15726149
EAN	8903094045624
Valid tyre size	460 / 85 R 26
Alternative size 1	18.4R26
LI / SI / PR	143 A8 / 143 B
TL/TT	TL
Brand	BKT
Tread pattern	RT 857
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	116,56
Recommended rim size	DW15L
Permitted rim size	W14L, W15L, W16L,DW16L
Maximum air pressure [bar].	1,60
Section width (mm)	465
Outer diameter of tyre [mm].	1442
Stat. radius (SLR) [mm]	642
Rolling circumference [mm].	4297
Tread depth (mm)	34,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	323.53
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 A8	2725	40		1,60	
143 B	2725	50		1,60	