

## TYRES

Product group	Tyres
Item number	15726180
Valid tyre size	340 / 85 R 28
LI / SI / PR	127 A8 / 127 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp  
■ ■ ● Moving Professionals

**BKT**  
GROWING TOGETHER

## Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

## Technical Informations

Item number	15726180
EAN	8903094021611
Valid tyre size	340 / 85 R 28
Alternative size 1	13.6R28
LI / SI / PR	127 A8 / 127 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	67,97
Recommended rim size	12
Permitted rim size	11
Maximum air pressure [bar].	1,60
Section width (mm)	353
Outer diameter of tyre [mm].	1289
Stat. radius (SLR) [mm]	588
Rolling circumference [mm].	3890
Tread depth (mm)	44,0
Number of lugs	19x2
Lug width (mm)	33
Tyre capacity 75% [ltr.]	147
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
127 A8	1750	40		1,60	
127 B	1750	50		1,60	