

## TYRES

Product group	Tyres
Item number	15726280
Valid tyre size	320 / 85 R 32
LI / SI / PR	126 A8 / 126 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

## Technical Informations

Item number	15726280
EAN	8903094021598
Valid tyre size	320 / 85 R 32
Alternative size 1	12.4R32
LI / SI / PR	126 A8 / 126 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	68,06
Recommended rim size	W11
Permitted rim size	W9, W10
Maximum air pressure [bar].	1,60
Section width (mm)	329
Outer diameter of tyre [mm].	1357
Stat. radius (SLR) [mm]	621
Rolling circumference [mm].	4081
Tread depth (mm)	42,0
Number of lugs	22x2
Lug width (mm)	31
Tyre capacity 75% [litr.]	138.75
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
126 A8	1700	40		1,60	
126 B	1700	50		1,60	