

TYRES

Product group	Tyres
Item number	15726300
Valid tyre size	420 / 85 R 34
LI / SI / PR	142 A8 / 142 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726300
EAN	8903094021741
Valid tyre size	420 / 85 R 34
Alternative size 1	16.9R34
LI / SI / PR	142 A8 / 142 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	116,84
Recommended rim size	W15L
Permitted rim size	W13, W14L
Maximum air pressure [bar].	1,60
Section width (mm)	438
Outer diameter of tyre [mm].	1578
Stat. radius (SLR) [mm]	709
Rolling circumference [mm].	4702
Tread depth (mm)	49,0
Lug width (mm)	36
Tyre capacity 75% [ltr.]	284.25
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40		1,60	
142 B	2650	50		1,60	