

TYRES

Product group	Tyres
Item number	15726312
Valid tyre size	IF 580 / 80 R 34 CFO
LI / SI / PR	177 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris



Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.

Technical Informations

Item number	15726312
EAN	8903094044641
Valid tyre size	IF 580 / 80 R 34 CFO
LI / SI / PR	177 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	236,00
Recommended rim size	DW20B
Permitted rim size	DW21A, DW21B
Maximum air pressure [bar].	3,60
Section width (mm)	586
Tread width (mm)	540
Outer diameter of tyre [mm].	1792
Stat. radius (SLR) [mm]	810
Speed Radius Index (SRI)	850
Rolling circumference [mm].	5422
Tread depth (mm)	57,0
Number of lugs	23x2
Tyre capacity 75% [litr.]	570.75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
177 D	7300	65		3,60	