

## TYRES

Product group	Tyres
Item number	15726340
Valid tyre size	320 / 85 R 36
LI / SI / PR	128 A8 / 128 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

## Technical Informations

Item number	15726340
EAN	8903094021628
Valid tyre size	320 / 85 R 36
Alternative size 1	12.4R36
LI / SI / PR	128 A8 / 128 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	74,00
Recommended rim size	W11
Permitted rim size	W9, W10
Maximum air pressure [bar].	1,60
Section width (mm)	329
Outer diameter of tyre [mm].	1458
Stat. radius (SLR) [mm]	672
Rolling circumference [mm].	4404
Tread depth (mm)	42,0
Number of lugs	23x2
Lug width (mm)	31
Tyre capacity 75% [ltr.]	152.25
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 A8	1800	40		1,60	
128 B	1800	50		1,60	