

## TYRES

Product group	Tyres
Item number	15726360
Valid tyre size	320 / 85 R 38
LI / SI / PR	143 A8 / 143 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp  
■ ■ ● Moving Professionals

**BKT**  
GROWING TOGETHER

## Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

## Technical Informations

Item number	15726360
EAN	8903094039593
Valid tyre size	320 / 85 R 38
Alternative size 1	12.4R38
LI / SI / PR	143 A8 / 143 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	84,00
Recommended rim size	W10
Permitted rim size	W9, W11, DW11
Maximum air pressure [bar].	3,60
Section width (mm)	319
Outer diameter of tyre [mm].	1509
Stat. radius (SLR) [mm]	700
Rolling circumference [mm].	4580
Tread depth (mm)	42,0
Number of lugs	24x2
Tyre capacity 75% [ltr.]	148.39
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 A8	2725	40		3,60	
143 B	2725	50		3,60	