

TYRES

Product group	Tyres
Item number	15726380
Valid tyre size	380 / 85 R 38
LI / SI / PR	139 A8 / 139 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726380
EAN	8903094030552
Valid tyre size	380 / 85 R 38
Alternative size 1	14.9R38
LI / SI / PR	139 A8 / 139 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	109,89
Recommended rim size	W12
Permitted rim size	W11, W13
Maximum air pressure [bar].	1,60
Section width (mm)	380
Outer diameter of tyre [mm].	1611
Stat. radius (SLR) [mm]	736
Rolling circumference [mm].	4842
Tread depth (mm)	45,0
Number of lugs	24x2
Tyre capacity 75% [ltr.]	247.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
139 A8	2430	40		1,60	
139 B	2430	50		1,60	