

TYRES

Product group	Tyres
Item number	15726382
Valid tyre size	VF 380 / 85 R 38
LI / SI / PR	161 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Excellent plant and soil protection allows yield increases.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent ride comfort and high machine stability.

Technical Informations

Item number	15726382
EAN	8903094045303
Valid tyre size	VF 380 / 85 R 38
LI / SI / PR	161 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	132,00
Recommended rim size	W13
Permitted rim size	W12
Maximum air pressure [bar].	3,20
Section width (mm)	380
Tread width (mm)	326
Outer diameter of tyre [mm].	1602
Stat. radius (SLR) [mm]	730
Speed Radius Index (SRI)	775
Rolling circumference [mm].	4830
Tread depth (mm)	45,0
Number of lugs	28x2
Tyre capacity 75% [ltr.]	230.84
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 D	4625	65		3,20	