

TYRES

Product group	Tyres
Item number	15726403
Valid tyre size	480 / 80 R 38
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726403
EAN	8903094045341
Valid tyre size	480 / 80 R 38
Alternative size 1	18.4R38
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	147,67
Recommended rim size	W16L
Permitted rim size	W14L, W15L
Maximum air pressure [bar].	1,60
Section width (mm)	475
Outer diameter of tyre [mm].	1747
Stat. radius (SLR) [mm]	785
Rolling circumference [mm].	5161
Tread depth (mm)	54,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	380.51
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		1,60	
149 B	3250	50		1,60	