

TYRES

| | |
|-----------------|----------------------|
| Product group | Tyres |
| Item number | 15726414 |
| Valid tyre size | IF 650 / 85 R 38 CFO |
| LI / SI / PR | 179 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax Force |



Notes and features

- BKT Agrimax Force is an IF tyre for high performance tractors with more than 250 hp.
- It offers 20% higher load capacity at the same air pressure or the same load capacity at 20% lower air pressure compared to a standard tyre.
- The large contact area enables a uniform distribution of ground pressure and therefore optimum soil protection.
- Its strong polyester belt carcass provides good traction and stability on all surfaces and long tyre life.
- The tyre guarantees driving comfort in the field and during transport trips on the road without the need to adjust the air pressure.

Technical Informations

| | |
|------------------------------|----------------------|
| Item number | 15726414 |
| EAN | 8903094051236 |
| Valid tyre size | IF 650 / 85 R 38 CFO |
| LI / SI / PR | 179 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax Force |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 362,20 |
| Recommended rim size | DW23B |
| Permitted rim size | DW20B, DW21B |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 663 |
| Tread width (mm) | 610 |
| Outer diameter of tyre [mm]. | 2071 |
| Stat. radius (SLR) [mm] | 927 |
| Speed Radius Index (SRI) | 975 |
| Rolling circumference [mm]. | 6106 |
| Tread depth (mm) | 64,5 |
| Number of lugs | 23x2 |
| Tyre capacity 75% [litr.] | 838.1 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 179 D | 7750 | 65 | | 2,40 | |