

TYRES

Product group	Tyres
Item number	15726420
Valid tyre size	480 / 80 R 42
LI / SI / PR	151 A8 / 151 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726420
EAN	8903094021796
Valid tyre size	480 / 80 R 42
Alternative size 1	18.4R42
LI / SI / PR	151 A8 / 151 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	172,56
Recommended rim size	W16A
Permitted rim size	DW16A, DD16, DD16L, DW16L, W16L
Maximum air pressure [bar].	1,60
Section width (mm)	479
Outer diameter of tyre [mm].	1835
Stat. radius (SLR) [mm]	835
Rolling circumference [mm].	5495
Tread depth (mm)	54,0
Number of lugs	22x2
Lug width (mm)	41
Tyre capacity 75% [ltr.]	421.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		1,60	
151 B	3450	50		1,60	