

## TYRES

Product group	Tyres
Item number	15726430
Valid tyre size	520 / 85 R 42
LI / SI / PR	157 A8 / 157 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

**Technical Informations**

Item number	15726430
EAN	8903094021819
Valid tyre size	520 / 85 R 42
Alternative size 1	20.8R42
LI / SI / PR	157 A8 / 157 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	196,84
Recommended rim size	DW16L
Permitted rim size	W16A, DD16, DW18A, DD18, W18A, DD18L
Maximum air pressure [bar].	1,60
Section width (mm)	516
Outer diameter of tyre [mm].	1951
Stat. radius (SLR) [mm]	858
Rolling circumference [mm].	5782
Tread depth (mm)	57,0
Number of lugs	22x2
Lug width (mm)	45
Tyre capacity 75% [litr.]	547.5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 A8	4125	40		1,60	
157 B	4125	50		1,60	