

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 15726433 |
| Valid tyre size | 520 / 85 R 42 |
| LI / SI / PR | 168 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax Teris |



Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.

Technical Informations

| | |
|------------------------------|--|
| Item number | 15726433 |
| EAN | 8903094044634 |
| Valid tyre size | 520 / 85 R 42 |
| LI / SI / PR | 168 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax Teris |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 232,56 |
| Recommended rim size | DW16L |
| Permitted rim size | W15L, DW15L, DD16L, W16L, DD18L, DW18L, W18L |
| Maximum air pressure [bar]. | 3,20 |
| Section width (mm) | 516 |
| Tread width (mm) | 480 |
| Outer diameter of tyre [mm]. | 1951 |
| Stat. radius (SLR) [mm] | 890 |
| Speed Radius Index (SRI) | 925 |
| Rolling circumference [mm]. | 5851 |
| Tread depth (mm) | 57,0 |
| Number of lugs | 22x2 |
| Tyre capacity 75% [litr.] | 545.85 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 168 D | 5600 | 65 | | 3,20 | |