

TYRES

Product group	Tyres
Item number	15726490
Valid tyre size	520 / 85 R 50
LI / SI / PR	165 A8 / 165 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726490
EAN	8903094057993
Valid tyre size	520 / 85 R 50
Alternative size 1	20.8R50
LI / SI / PR	165 A8 / 165 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	261,06
Recommended rim size	DW16L
Permitted rim size	18, DW15L
Maximum air pressure [bar].	2,40
Section width (mm)	516
Outer diameter of tyre [mm].	2154
Stat. radius (SLR) [mm]	992
Rolling circumference [mm].	6472
Tread depth (mm)	56,0
Number of lugs	25x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 A8	5150	50		2,40	
165 B	5150	50		2,40	