

TYRES

Product group	Tyres
Item number	15726535
Valid tyre size	11L R 16
LI / SI / PR	122 A8 / 122 B
TL/TT	TL
Brand	BKT
Tread pattern	Agro Industrial RT 747



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Wide contact surface ensures optimum ground protection.
- Reduced rolling resistance lowers fuel consumption.
- New lug design with optimal traction.
- Sturdy carcass construction offers high load capacity reserves.
- Special rubber compound ensures long service life.

Technical Informations

Item number	15726535
EAN	8903094062737
Valid tyre size	11L R 16
LI / SI / PR	122 A8 / 122 B
TL/TT	TL
Brand	BKT
Tread pattern	Agro Industrial RT 747
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	30,50
Recommended rim size	W8
Permitted rim size	W10L
Maximum air pressure [bar].	2,20
Section width (mm)	290
Outer diameter of tyre [mm].	850
Stat. radius (SLR) [mm]	371
Rolling circumference [mm].	2497
Tread depth (mm)	24,5
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
122 A8	1500	40		2,20	
122 B	1500	50		2,20	