

TYRES

Product group	Tyres	
Item number	15726539	
Valid tyre size	260 / 70 R 16	
LI / SI / PR	109 A8 / 109 B	
TL/TT	TL	
Brand	BKT	
Tread pattern	Agrimax Turf RT 333	





Notes and features

- The BKT Agrimax Turf RT 333 is a radial tyre for small tractors in gardening, wine or fruit cultivation.
- Its rounded tyre shoulder ensures low soil compaction and prevents damage to delicate soils.
- Thanks to the special directional block tread and the high tread pattern depth, the tyre provides good traction in the field and on the road and a long service life.
- Furthermore, the tyre has excellent self-cleaning properties.



Technical Informations

Item number	15726539
EAN	8903094067909
Valid tyre size	260 / 70 R 16
LI / SI / PR	109 A8 / 109 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Turf RT 333
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	23,65
Recommended rim size	W8
Permitted rim size	W8L, W9
Maximum air pressure [bar].	2,40
Section width (mm)	258
Outer diameter of tyre [mm].	770
Stat. radius (SLR) [mm]	348
Rolling circumference [mm].	2287
Tread depth (mm)	22,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
109 A8	1030	40		2,40	
109 B	1030	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.