

TYRES

Product group	Tyres
Item number	15726543
Valid tyre size	220 / 70 R 16
LI / SI / PR	99 A8 / 99 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.



Technical Informations

Item number	15726543
EAN	8903094045365
Valid tyre size	220 / 70 R 16
LI / SI / PR	99 A8 / 99 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	18,20
Recommended rim size	W7
Permitted rim size	W8
Maximum air pressure [bar].	2,40
Section width (mm)	221
Outer diameter of tyre [mm].	715
Stat. radius (SLR) [mm]	324
Rolling circumference [mm].	2145
Tread depth (mm)	26,0
Number of lugs	17x2
Tyre capacity 75% [ltr.]	24.47
E-Ready	No



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
99 A8	775	40		2,40	
99 B	775	50		2,40	