

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 15726560 |
| Valid tyre size | 280 / 70 R 16 |
| LI / SI / PR | 112 A8 / 112 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 765 |



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 15726560 |
| EAN | 8903094021895 |
| Valid tyre size | 280 / 70 R 16 |
| LI / SI / PR | 112 A8 / 112 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 765 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 26,16 |
| Recommended rim size | W9 |
| Permitted rim size | W8, W8L, W10 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 282 |
| Outer diameter of tyre [mm]. | 798 |
| Stat. radius (SLR) [mm] | 356 |
| Rolling circumference [mm]. | 2370 |
| Tread depth (mm) | 32,0 |
| Lug width (mm) | 25 |
| Tyre capacity 75% [litr.] | 45 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 112 A8 | 1120 | 40 | | 2,40 | |
| 112 B | 1120 | 50 | | 2,40 | |